

Enterprise Products



The MSI Experience...When Support Counts!





Our Heritage

MacLean Senior Industries (MSI), formed by merging of the communications business of MacLean Power Systems with Senior Industries, offers a comprehensive line of Datacomm Products. This includes; grounding/bonding clamps and connectors, distribution/drive/bridle rings, J Hooks and tools for the efficient and reliable installation of wiring and networks.

MSI has proudly served the communications market for over 40 years, creating products and developing solutions to meet the specific requirements of our customers. We continue to develop close relationships with our customers by supplying top quality products at competitive prices, with the highest level of service.

Design/Product Development

If the product you need is not listed in our catalog or on our web site, please contact us. Experienced MSI professionals with a problem solving attitude, backed by the most recent technological capabilities, will respond to your unique product need with an innovative and cost effective solution that can be produced to meet your budget and timetable. With over 50 patents and the track record of developing hundreds of proven products, you can trust us to provide exactly what you need, when you need it.

Worldwide Manufacturing Resources

MSI is an American company with global manufacturing capabilities. We have 13 production facilities worldwide, including 7 factories in the U.S. alone. We can ensure that your product needs will be met when you need them. Our global manufacturing strategy allows for the optimal combination of quality, cost and delivery.

Customer Service/Distribution

MSI has two main distribution hubs in Wood Dale, Illinois and Memphis, Tennessee, making sure that parts are available when you need them.

Quality You Can Depend On

MSI is ISO 9001 certified. We won't produce a product that doesn't meet our high quality and reliability standards, per the product specifications. If you have a question about any MSI product, we will be there to respond to it.

For technical support, installation information and special requirements please contact our Inside Sales Team at: 1-800-350-1650, or via e-mail at: sales@macleansenior.com.

SPLIT BOLTS

- High strength corrosion resistant copper alloy connectors for use in bonding applications
- Designed to provide high clamping force
- Split bolt will accept on any combination of two conductors shown in the chart below
- UL and CUL listed

| Part Number | Size | | of Equal and Tap Max. | Min. Tap with One Max. Main | Package Qty | Package Weight | Carton Qty | Carton Weight |
|----------------|------|---------|-----------------------------|-----------------------------------|----------------|-------------------|---------------|------------------|
| SI-2002 | 2 | #6 SOL | #2 STR | #14 STR | 50 | 10 Lbs. | 400 | 44 Lbs. |
| SI-2004 | 4 | #8 SOL | #4 SOL | #16 SOL | 100 | 7 Lbs. | 800 | 53 Lbs. |
| SI-2006 | 6 | #10 SOL | #6 SOL | #16 SOL | 100 | 5 Lbs. | 800 | 40 Lbs. |
| SI-2008 | 8 | #16 STR | #8 STR | #16 STR | 200 | 6 Lbs. | 1600 | 47 Lbs. |



GROUND ROD CLAMP

- Used to provide a solderless connection between a #6 ground wire and a ground rod
- · Clamps are constructed of cast bronze
- Available in vibration proof, anti-loosening versions
- · UL and CUL listed



| Part Number | Ground Rod Diameter | Bolt Hex Size | Conductor Range | Carton Oty | Carton Size | Carton Weight |
|----------------|------------------------|--------------------------------|--------------------|---------------|----------------|------------------|
| SI-0038C | 5/8" | 1/2" | #10 SOL - #1/0 STR | 400 | 10"x 9"x 9" | 42 Lbs. |
| SI-2142 | 5/8" | ⁹ / ₁₆ " | #12 SOL - #6 SOL | 25 | 6" x 4"x 4" | 11 Lbs. |

KUL BONDING CLAMP

- Constructed of high strength copper alloy
- Installation does not require removal of bolt
- Tin plated for use with dissimilar metals
- Installs with standard terminal wrench
- UL and CUL listed





STRUCTURE I-BEAM GROUND CLAMP

- Used to provide an electrical connection to beam structures
- High strength bronze casting
- Will accept wire range from #14 AWG to #6 AWG including bonding ribbon
- · UL and CUL listed

| Part Number | Carton Qty | Master Oty | Carton Size | Carton Weight |
|-------------|------------|------------|---------------|---------------|
| SI-2145 | 20 | 200 | 16" x 8" x 6" | 56 Lbs. |
| SI-2145A | 20 | 200 | 16" x 8" x 6" | 56 Lbs. |



BRONZE VISE CONNECTOR

- Used to provide a solderless connection between ground wires
- Vise-type connector made of corrosion resistant, high strength bronze
- · Fast, easy installation

- · Vibration proof connection
- V-grooves properly align the conductors for maximum engagement
- UL and CUL listed
- 1/4" 28 bolt size, 3/8" hex



| Part | Conductor Range AWG | | | Package | Carton | Carton | Carton |
|-----------|---------------------|---------------|----------------|---------|--------|----------------|---------|
| Number | Min. Pair | Max. Pair | Set Screw/Stud | Oty | Qty | Size | Weight |
| SI-0082JK | #8 SOL to #5 SOL | 1/0 to #4 SOL | #6 to #14 SOL | 50 | 350 | 10" x 10" x 6" | 45 Lbs. |

DISTRIBUTION CONNECTORS

- Design allows for easy tapping or covering of the connection
- Designed to meet all ANSI specifications
- Clamp will close on any combination of two conductors shown in the chart below
- UL and CUL listed



| | Conductor Range | | Range | Approximate | | | | | |
|---------|-----------------|-----|-------|--|-----------------------------------|------|--------|---------|--|
| Part | N | Лах | Min | Dimensions | Bolt | Hex | Carton | Carton | |
| Number | SOL | STR | SOL | | Size | (In) | Qty | Weight | |
| SI-2173 | #1/0 | #1 | #8 | 1 ¹ / ₂ " x 1 ³ / ₈ " x 1" | ⁵ / ₁₆ - 24 | 9/16 | 50 | 12 Lbs. | |

- Vise-type bronze connector
- Interlocking components to ensure a long term, vibration proof connection
- One piece, side opening design to eliminate loose parts, cross threading, and ease of installation on run conductor
- Can be used on structures, cabinets, and enclosures for grounding applications
- Connector will close on any combination of two conductors listed within the range shown in the chart below
- UL and CUL listed



| Part | Conductor Range | Bolt Thread | Bolt Hex | Package | Carton | Carton | Carton |
|---------|-----------------|-------------------------------------|-------------------|---------|--------|---------------------|---------|
| Number | | Size | Size | Qty | Oty | Size | Weight |
| SI-2179 | #8 #1/0 | ⁵ / ₁₆ " - 24 | ⁹ /16" | 30 | 240 | 10" x 81/2" x 71/2" | 38 Lbs. |

GROUNDING CONNECTOR

- Used to provide a solderless connection between ground wires
- Vise-type connectors made of corrosion resistant, high strength bronze
- · Fast, easy installation

- Vibration proof connection
- V-grooves properly align the conductors for maximum engagement
- UL and CUL listed



| Part Number | Conductor F SOL | | olt Size Hex (| Carton Qty | Carton Size | Carton Weight |
|----------------|--------------------|--------|---------------------|------------|----------------|------------------|
| SI-2169 | #4 | #4 5/- | 16 - 24 9/16 | 350 | 10" x 10" x 6" | 56 Lbs. |
| SI-2170 | #6 | #8 5/- | 16 - 28 3/8 | 500 | 9" x 9" x 6" | 40 l bs. |

WATER PIPE CLAMP


- · Ideal for bonding copper ground wire to copper pipe and conduit
- Accepts from #14 to #6 AWG copper wire
- · UL and CUL listed

| Part Number | r Size | Material | Carton Oty | Carton Size | Carton Weight |
|-------------|------------------|----------|------------|--------------|---------------|
| SI-5948G | 1/2" - 3/4" - 1" | Bronze | 250 | 9" x 7" x 6" | 48 Lbs. |



UNIVERSAL GROUND STRAP

- Positive grounding connection to water pipes, electrical conduits & ground rods
- Features new captive nut, which prevents loss of nut during installation
- Features patented curved nut, which gives a more reliable, secure connection to pipe
- Set-screw stud assembly is compatible with a standard terminal wrench
- Set-screw stud assembly allows ground wire changes without loosening clamp
- Available in 6, 9, or 12 inch lengths with copper or galvanized steel straps
- Available with a penetrater option to ensure a positive, reliable ground
- SI-0954 Premium type ground straps accommodate up to #6 AWG
- UL and CUL listed
- Patented



SI-0954 series clamps also available with penetrator. To order, add "P" suffix



| Part Number | Туре | Strap Material | Strap Length | Pipe Size Dia. (In) | Package Qty | Carton Qty | Carton Size | Carton Weight |
|----------------|---------|-------------------|-----------------|------------------------------|----------------|---------------|-----------------|------------------|
| SI-0954-6 | Premium | Copper | 6" | ¹ /2"- 1 " | 25 | 100 | 4¼" x 4¼" x 12" | 2 Lbs. |
| SI-0954-9 | Premium | Copper | 9" | 1/2"- 21/4" | 25 | 100 | 4¼" x 4¼" x 12" | 3 Lbs. |
| SI-0954-12 | Premium | Copper | 12" | 1/2"- 3" | 25 | 100 | 4¼" x 4¼" x 12" | 4 Lbs |
| SI-0954G-6 | Premium | Galvanized Steel | 6" | ¹ /2"- 1" | 25 | 100 | 4¼" x 4¼" x 12" | 2 Lbs. |
| SI-0954G-9 | Premium | Galvanized Steel | 9" | 1/2"- 21/4" | 25 | 100 | 4¼" x 4¼" x 12" | 3 Lbs. |
| SI-0954G-12 | Premium | Galvanized Steel | 12" | 1/2"- 3" | 25 | 100 | 4¼" x 4¼" x 12" | 4 Lbs. |

COMPRESSION LUGS

- Constructed of premium, high conductivity copper, electro-tin plated
- Optimal material ductility provides secure crimp with superior tension and pull out resistance
- Wire range of #8 4/0 to meet all Telecommunications applications
- Color coded for easy identification of corresponding wire sizes
- 1 and 2 hole lug configurations for attachment to common stud sizes.
- Multiple bend angles, including 45° and 90°
- · Available in standard, long and short barrel lengths
- Available with inspection window to confirm wire insertion
- Narrow tongue options available.
- Compatible with industry standard compression tools and crimp dies
- Made in the U.S.A.
- Meets or exceeds UL 486A and ANSI C119.4 requirements



MSI stocks hundreds of different compression lugs, please contact us with your compression lug requirements.

J HOOKS AND J HOOK TREES

- Provides the ability to organize and support large numbers of cables
- Maintains optimal cable performance by preventing damage associated with point loading
- Wide base prevents pinch points and allows for cable to follow natural bends
- Provides an inexpensive alternative to cable trays
- Ideal design for use with a range of cables including fiber optic, CAT 5E, 6 and 7, among others
- Cable retaining clip included
- Variety of options allow hooks to be attached to vertical or overhead surfaces
- · Available in Steel or Stainless Steel



| Part Number | Description | CAT 5E Cable Capacity | Material |
|------------------|---|-----------------------|---------------------------|
| SI-6935-12 | J Hook, ³ / ₄ " | 20 | Steel, Zinc Electroplated |
| SI-6935-21 | J Hook, 1 ⁵ / ₁₆ " | 40 | Steel, Zinc Electroplated |
| SI-6935-32 | J Hook, 2" | 80 | Steel, Zinc Electroplated |
| SI-6935-64 | J Hook, 4" | 300 | Steel, Zinc Electroplated |
| SI-6935-12-SS | J Hook, ³ / ₄ " | 20 | Stainless Steel |
| SI-6935-21-SS | J Hook, 1-5/16" | 40 | Stainless Steel |
| SI-6935-32-SS | J Hook, 2" | 80 | Stainless Steel |
| SI-6935-64-SS | J Hook, 4" | 300 | Stainless Steel |
| SI-6935-12-AB | J Hook, 3/4" with overhead mount bracket | 20 | Steel, Zinc Electroplated |
| SI-6935-21-AB | J Hook, 1-5/16" with overhead mount bracket | 40 | Steel, Zinc Electroplated |
| SI-6935-32-AB | J Hook, 2" with overhead mount bracket | 80 | Steel, Zinc Electroplated |
| SI-6935-32-AB | J Hook, 4" with overhead mount bracket | 300 | Steel, Zinc Electroplated |
| SI-6935-12-AB-SS | J Hook, 3/4" with overhead mount bracket | 20 | Stainless Steel |
| SI-6935-21-AB-SS | J Hook, 1-5/16" with overhead mount bracket | 40 | Stainless Steel |
| SI-6935-32-AB-SS | J Hook, 2" with overhead mount bracket | 80 | Stainless Steel |
| SI-6935-32-AB-SS | J Hook, 4" with overhead mount bracket | 300 | Stainless Steel |
| SI-6935T-212 | J Hook Tree, 1-5/16" with 2 Hooks | 80 | Steel, Zinc Electroplated |
| SI-6935T-214 | J Hook Tree, 1-5/16" with 4 Hooks | 160 | Steel, Zinc Electroplated |
| SI-6935T-216 | J Hook Tree, 1-5/16" with 6 Hooks | 240 | Steel, Zinc Electroplated |
| SI-6935T-322 | J Hook Tree, 2" with 2 Hooks | 160 | Steel, Zinc Electroplated |
| SI-6935T-324 | J Hook Tree, 2" with 4 Hooks | 320 | Steel, Zinc Electroplated |
| SI-6935T-326 | J Hook Tree, 2" with 6 Hooks | 480 | Steel, Zinc Electroplated |

BASEBOARD CLIPS

- · Used to secure coaxial or twisted pair cable to baseboard
- · Steel construction, enamel coated
- Patent pending
- Add suffix to part number to denote color: N = Neutral, W = White, B = Black

| Part Number | Cable Size | Carton Qty | Carton Size | Carton Weight |
|-------------|------------|------------|--------------|---------------|
| SI-0991 | RG 6 | 1000 | 6" x 4" x 4" | 4 Lbs. |
| SI-0992 | RG 6 Quad | 1000 | 6" x 4" x 4" | 4 Lbs. |
| SI-0993 | Telephone | 1000 | 6" x 4" x 4" | 4 Lbs. |
| SI-0994 | Category 5 | 1000 | 6" x 4" x 4" | 4 Lbs. |



BRIDLE RINGS


- Used to secure drop wire to wood, masonry or metal surfaces
- · Constructed of high quality steel, mechanically plated
- A and C bridle rings have wood screw threads
- B, K, M and R bridle rings have machine screw threads




| Part Number | Style | Eye Dia. | Thread Size | Package Qty | Carton Qty | Carton Size | Carton Weight |
|-------------|-------|--------------------|-------------|-------------|------------|----------------|---------------|
| SI-0060 | В | 5/8" | 10-24 | 25 | 1000 | 12" x 12" x 8" | 28 Lbs. |
| SI-0061 | С | ⁷ ⁄8" | 10 | 30 | 750 | 12" x 12" x 8" | 30 Lbs. |
| SI-0062 | С | 1 ⁵ ⁄8" | 14 | 25 | 300 | 12" x 12" x 8" | 40 Lbs. |
| SI-6651 | Α | 15⁄8" | 16 | 25 | 600 | 12" x 12" x 8" | 40 Lbs. |
| SI-6653 | С | 1¼" | 14 | 25 | 500 | 12" x 12" x 8" | 35 Lbs. |
| SI-6666 | K | 3/4" | 10-24 | 25 | 1200 | 12" x 12" x 8" | 45 Lbs. |
| SI-6667 | M | 1 ½" | 10-24 | 25 | 750 | 12" x 12" x 8" | 41 Lbs. |
| SI-6669 | R | 15⁄8" | 1/4-24 | 25 | 525 | 12" x 12" x 8" | 44 Lbs. |

DISTRIBUTION RINGS

- Used to provide support for wires in building cable terminals and distribution closets
- · Constructed of die cast aluminum










| Part Number | (A) | Dian (B) | neter (C) | (D) | Box Qty | Carton Qty | Carton Size | Carton Weight |
|----------------|-------|-------------|--------------|-------|------------|---------------|-----------------|------------------|
| SI-4753 | 4.88" | 1.87" | 3.13" | 2.74" | 25 | 500 | 20" x 17" x 11" | 60 Lbs. |
| SI-4754 | 6.12" | 3.11" | 4.39" | 3.74" | 25 | 250 | 23" x 14" x 11" | 40 Lbs. |
| SI-4755 | 8.12" | 5.12" | 6.38" | 3.74" | 25 | 250 | 23" x 18" x 11" | 50 Lbs. |
| SI-4753-M | 2.44" | .94" | 1.57" | 2.74" | 50 | 1000 | 20" x 17" x 11" | 60 Lbs. |
| SI-4754-M | 3.06" | 1.56" | 2.20" | 3.74" | 50 | 500 | 23" x 14" x 11" | 40 Lbs. |
| SI-4755-M | 4.06" | 2.56" | 3.19" | 3.74" | 50 | 500 | 23" x 18" x 11" | 50 Lbs. |

DRIVE RINGS

- Used for temporary or permanent support of wires
- Constructed of high quality steel, hot-dip galvanized for durability





| Part Number | Eye Diameter | (A) | (B) | Dime | ensions (D) | (E) | (F) | Package Qty | Carton Qty | Carton Size | Carton Weight |
|----------------|--------------------|----------------------|-------|-----------------------------|---------------------|---------------------------------|-------|----------------|---------------|---|------------------|
| SI-6861 | 1/2" | 21/16" | .125" | 1 ³ /8" | 3/4" | 1/2" | .120" | 50 | 500 | 16" x 8" x 6" | 23 Lbs. |
| SI-6862 | ⁵ /8" | 21/4" | .135" | 1 7⁄16" | 1 ¹ /8" | 5/8" | .165" | 50 | 500 | 16" x 8" x 6" | 25 Lbs. |
| SI-6862L | 5/8" | 23/4" | .135" | 1 ¹⁵ /16" | 1 ½" | 5/8" | .165" | 50 | 400 | $9^{1/2}$ " x $9^{1/2}$ " x $7^{1/2}$ " | 14 Lbs. |
| SI-6863 | ⁷ /8" | 2 ⁹ /16" | .177" | 1 ¹ /2" | 2 ¹ /16" | ⁷ /8" | .165" | 25 | 200 | 16" x 8" x 6" | 11 Lbs. |
| SI-6863L | ⁷ /8" | 3 ¹ /16" | .177" | 2" | 2 ¹ /16" | ⁷ /8" | .165" | 25 | 200 | 14" x 4½" x 7" | 12 Lbs. |
| SI-6864 | 1 ¹ /4" | 2 ¹⁵ /16" | .192" | 1 ⁵ /8" | 23/4" | 1 ¹ /4" | .203" | 25 | 100 | 6" x 8" x 14" | 10 Lbs. |
| SI-6864L | 1 ¹ /4" | 21/8" | .192" | 3 ⁷ /16" | 23/4" | 1 ¹ / ₄ " | .203" | 25 | 100 | 14" x 7½" x 5¾" | 10 Lbs. |

WALL PLATES

- · Single hole wall plate
- Durable, heavy-duty plastic, ivory color
- Fits standard electrical outlets

• Other sizes and configurations available on request

| Part Number | Carton Qty | Carton Size | Carton Weight |
|-------------|------------|--------------|---------------|
| SI-WP-100 | 50 | 5" x 3" x 2" | 1 Lb. |



HANDI-REEL

- Super easy reel installation
- · Makes one-man installations easier
- Lightweight aluminum frame
- Locks in open position
- · Safety latch prevents spindle from detaching when inverted
- Anti-skid pads
- Designed to support 1 or 2 man carry
- Sturdy enough for outdoor installations
- Patented



| Part Number | Туре | Max Reel Diameter | Max Reel Width | Spindle Diameter | Carton Oty | Carton Size | Carton Weight |
|----------------|------------|----------------------|-------------------|---------------------|---------------|-----------------|------------------|
| SI-1500 | Handi-Reel | 19" | 13" | 5/8" | 1 | 15½" x 15" x 4" | 4 Lbs. |
| SI-1550 | Handi-Reel | 25" | 16" | 5/8" | 1 | 19" x 18" x 6" | 6 Lbs. |

TERMINAL WRENCH

- Used to install drop hardware
- $\frac{3}{8}$ " and $\frac{7}{16}$ " sockets

| Part Number | Package Oty | Weight |
|-------------|-------------|--------|
| SI-7195 | 1 | 3 l hs |





MACLEAN SENIOR INDUSTRIES

MacLean Senior Industries, LLC

610 Pond Drive, Wood Dale, IL 60191 Phone: **800-350-1650** Fax: **630-350-1654**

Web: www.macleansenior.com
E-mail: sales@macleansenior.com