

1

2

3

4

5

COMPONENT SPECIFICATION

USE OR REPRODUCTION OF THIS DRAWING FOR THE PURPOSE OF MANUFACTURING THIS ARTICLE OR ANY ARTICLES SHOWN FOR ANY PURPOSE IS STRICTLY PROHIBITED WITHOUT WRITTEN PERMISSION FROM SENIOR INDUSTRIES, INC.

SPECIFICATIONS

ELECTRICAL

CONTACT RATING: 50mA AT 12 VDC
 CONTACT RESISTANCE: 100 MILLIOHMS MAX.
 INSULATION RESISTANCE: 100 MEGOHMS MIN. AT 100 VDC
 DIELECTRIC STRENGTH: 250 VAC FOR 1 MINUTE

MECHANICAL

OPERATING LIFE: 200,000 CYCLES MIN.
 TRAVEL: 0.25 ±0.1 mm

ENVIRONMENTAL

OPERATING TEMPERATURE: -20°C TO +70°C
 STORAGE TEMPERATURE: -30°C TO +80°C

MATERIAL

HOUSING: PA66 G30, UL94HB, BLACK
 ACTUATOR: PA66 G30, UL94HB, BLACK
 TERMINALS: 0.3MM BRASS, SILVER PLATED
 CONTACT: STAINLESS STEEL, SILVER CLAD



SENIOR INDUSTRIES, INC.

DESIGNED:			SYM.	DATE:	DESCRIPTION OF REVISIONS:	DRAWN:	APPD:	PART NO:	SRT-KRS-0606-XXX
DRAWN:	RB	12/29/03	▲	12.29.03	NEW	RB	TF	TITLE:	TACT SWITCH
CHECKED:	GAT	08/02/05	▲	08.02.05	New Indicator, Dist bet. term. corr to 6.5, UL94HB	GAT	JF		
APPROVED:	JF	08/03/05	▲	.	.				
			▲	.	.				
3RD ANGLE		UNIT:	mm	SCALE:		REV:	B	AS ANGLES:	±
								SHEET:	2 OF 2

A

B

C